

```
MS-DOS 模式
C:\WINDOWS>ping www.ncue.edu.tw

Pinging ultra.ncue.edu.tw [163.23.225.200] with 32 bytes of data:

Reply from 163.23.225.200: bytes=32 time<10ms TTL=254
Reply from 163.23.225.200: bytes=32 time<10ms TTL=254
Reply from 163.23.225.200: bytes=32 time<10ms TTL=254
Reply from 163.23.225.200: bytes=32 time<10ms TTL=254

Ping statistics for 163.23.225.200:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\WINDOWS>
```

註：若出現Reply from 「IP」: bytes=32 time<10ms TTL=254表示兩點間的網路是通的，其中time表示回應時間，數值愈小網路愈快。

```
MS-DOS 模式
C:\WINDOWS>ping 10.1.1.1

Pinging 10.1.1.1 with 32 bytes of data:

Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 10.1.1.1:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\WINDOWS>_
```

註：若出現Request timed out，表示兩點間的網路是不通的。